

SCREW PEGS AUSTRALIA

Description and How to Use Instructions

The Hook Connector (Clip) Is Design Registered IP Rights and Patent Pending

Clips 10mm x 3mm Spring Grade 316 Stainless Steel .Tensile Strength = 1275 - 1480 MPA

Clips 12mm x 3mm Spring Grade 316 Stainless Steel .Tensile Strength = 1275 - 1480 MPA

These pegs are steel and galvanised. NOT PLASTIC. ALL WASHERS ARE 316 GRADE STAINLESS STEEL

The Pegs should be driven by an electric drill @ slow speed with an adjustable clutch set at middle of range .

ALL PEGS APART FROM 12mm REEFING PEGS MUST BE FITTED WITH 2 (TWO) WASHERS !

THE 2 WASHERS ACT AS A SLIP CLUTCH TO THE DRILL SOCKET AND THE CLIP OR EYELET

The 12mm x 300mm Reefing Pegs require one only 13mm x 30mm heavy duty washer

8mm Mat Pegs have a socket head size of 13mm

10mm Pegs have a socket head size of 16mm

12mm Pegs have a socket head size of 18mm

Pegs should generally be driven at an angle of 45 degrees to 60 degrees to the horizontal

Decrease this angle in shallow profile soils

In some places it may be necessary to pre- drill with a smaller diameter masonry drill bit

Make the starting point of the peg where you want the head or clip to finish

Thread lengths of Pegs

8mm x 130mm = 80mm

10mm x 200mm = 120mm

10mm x 250mm = 175mm

10mm x 300mm = 175mm

12mm x 300mm = 200mm

SIZES, USES & PACKS AVAILABLE

Heavy Duty Mat Pegs 8mm x 130mm Pack of 14 + 28 SS Washers = 8mm x 19mm

Skirt Pegs 10mm x 200mm Pack of 10 + 20SS Washers = 10mm x 21mm

Skirt Pegs 10mm x 200mm Pack of 10 + 20SS Washers = 10mm x 21mm + 10 of 10mm Spring Grade 316 Stainless Steel Clips

Annex Pegs 10mm x 250mm Pack of 10 + 20SS Washers = 10mm x 21mm

Annex Pegs 10mm x 250mm Pack of 10 + 20SS Washers = 10mm x 21mm + 10 of 10mm Spring Grade 316 Stainless Steel Clips

Annex Pegs 10mm x 300mm Pack of 10 + 20 SS Washers = 10mm x 21mm

Annex Pegs 10mm x 300mm Pack of 10 + 20 SS Washers = 10mm x 21mm + 10 of 10mm Spring Grade 316 Stainless Steel Clips

Reefing Pegs 12mm x 300mm Pack of 10 + 10 SS HD Washers = 13mm x 30mm

HD Pegs 12mm x 300mm Pack of 10 + 20 SS Washers = 12mm x 24mm + 10 of 12mm Spring Grade 316 Stainless Steel Clips

CLIPS 10mm Pack of 10

CLIPS 12mm Pack of 10

STARTER KIT

10 x 10mm x 250mm Pegs ; 4 x 10mm x 300mm Pegs ; 2 x 12mm x 300mm Pegs

Plus 28 of 10mm x 21mm 316 grade SS Washers & 2 of 13mm x 30mm HD 316 grade SS Washers

Plus 10 of 10mm 316 Spring Grade Stainless Steel Clips

MAGNETIC DRILL DRIVER SOCKETS

13mm Pack of 1

16mm Pack of 1

18mm Pack of 1

SCREW PEGS AUSTRALIA

Description and How to Use Instructions

The Hook Connector (Clip) Is Design Registered IP Rights and Patent Pending

Clips 10mm x 3mm Spring Grade 316 Stainless Steel.Tensile Strength = 1275 - 1480 MPA

Clips 12mm x 3mm Spring Grade 316 Stainless Steel.Tensile Strength = 1275 - 1480 MPA

These pegs are steel and galvanised. **NOT PLASTIC. ALL WASHERS ARE 316 GRADE STAINLESS STEEL**

The Pegs should be driven by an electric drill @ slow speed with an adjustable clutch set at middle of range .

ALL PEGS APART FROM 12mm REEFING PEGS MUST BE FITTED WITH 2 (TWO) WASHERS !

THE 2 WASHERS ACT AS A SLIP CLUTCH TO THE DRILL SOCKET AND THE CLIP OR EYELET

The 12mm x 300mm Reefing Pegs require one only 13mm x 30mm heavy duty washer

8mm Mat Pegs have a socket head size of 13mm

10mm Pegs have a socket head size of 16mm or 17mm (as marked on the website product page and packaging, due to product modification)

12mm Pegs have a socket head size of 18mm or 19mm (as marked on the website product page and packaging, due to product modification)

Pegs should generally be driven at an angle of 45 degrees to 60 degrees to the horizontal

Decrease this angle in shallow profile soils

In some places it may be necessary to pre- drill with a smaller diameter masonry drill bit

Make the starting point of the peg where you want the head or clip to finish

SCREW PEGS AUSTRALIA

Description and How to Use Instructions

The Hook Connector (Clip) Is Design Registered IP Rights and Patent Pending

Clips 10mm x 3mm Spring Grade 316 Stainless Steel.Tensile Strength = 1275 - 1480 MPA

Clips 12mm x 3mm Spring Grade 316 Stainless Steel.Tensile Strength = 1275 - 1480 MPA

These pegs are steel and galvanised. **NOT PLASTIC. ALL WASHERS ARE 316 GRADE STAINLESS STEEL**

The Pegs should be driven by an electric drill @ slow speed with an adjustable clutch set at middle of range .

ALL PEGS APART FROM 12mm REEFING PEGS MUST BE FITTED WITH 2 (TWO) WASHERS !

THE 2 WASHERS ACT AS A SLIP CLUTCH TO THE DRILL SOCKET AND THE CLIP OR EYELET

The 12mm x 300mm Reefing Pegs require one only 13mm x 30mm heavy duty washer

8mm Mat Pegs have a socket head size of 13mm

10mm Pegs have a socket head size of 16mm or 17mm (as marked on the website product page and packaging, due to product modification)

12mm Pegs have a socket head size of 18mm or 19mm (as marked on the website product page and packaging, due to product modification)

Pegs should generally be driven at an angle of 45 degrees to 60 degrees to the horizontal

Decrease this angle in shallow profile soils

In some places it may be necessary to pre- drill with a smaller diameter masonry drill bit

Make the starting point of the peg where you want the head or clip to finish

SCREW PEGS AUSTRALIA

Description and How to Use Instructions

The Hook Connector (Clip) Is Design Registered IP Rights and Patent Pending

Clips 10mm x 3mm Spring Grade 316 Stainless Steel.Tensile Strength = 1275 - 1480 MPA

Clips 12mm x 3mm Spring Grade 316 Stainless Steel.Tensile Strength = 1275 - 1480 MPA

These pegs are steel and galvanised. **NOT PLASTIC. ALL WASHERS ARE 316 GRADE STAINLESS STEEL**

The Pegs should be driven by an electric drill @ slow speed with an adjustable clutch set at middle of range .

ALL PEGS APART FROM 12mm REEFING PEGS MUST BE FITTED WITH 2 (TWO) WASHERS !

THE 2 WASHERS ACT AS A SLIP CLUTCH TO THE DRILL SOCKET AND THE CLIP OR EYELET

The 12mm x 300mm Reefing Pegs require one only 13mm x 30mm heavy duty washer

8mm Mat Pegs have a socket head size of 13mm

10mm Pegs have a socket head size of 16mm or 17mm (as marked on the website product page and packaging, due to product modification)

12mm Pegs have a socket head size of 18mm or 19mm (as marked on the website product page and packaging, due to product modification)

Pegs should generally be driven at an angle of 45 degrees to 60 degrees to the horizontal

Decrease this angle in shallow profile soils

In some places it may be necessary to pre- drill with a smaller diameter masonry drill bit

Make the starting point of the peg where you want the head or clip to finish